


OSIGHT SE DPP

Simple yet Extraordinary

	Enclosed Emitter Optic		Large Field of View
	Multi-Reticle System		DPP Footprint
	Side-Loading CR1620 Battery		Aspherical Lens



OSIGHT SE DPP

Simple yet Extraordinary

Market Applications

Concealed Carry, Self-Defense, Home Protection,
Everyday Carry, Training

UPC

6978095650346

DESCRIPTION

The Osight SE DPP is a premium enclosed-emitter pistol optic engineered for fast target acquisition, rugged durability, and dependable performance. Its fully enclosed optical system shields the emitter from dust, water, and debris, ensuring reliable operation in demanding conditions. A large 0.91" x 0.71" viewing window with advanced anti-reflective coatings provides a bright, expansive sight picture for faster target transitions and confident follow-up shots. The Multi-Reticle System allows users to instantly switch between a 2 MOA dot, 32 MOA circle, or dot-and-circle combination to suit a variety of shooting scenarios. Featuring a DPP footprint for broad compatibility and secure installation, the optic also incorporates a convenient side-loading CR1620 battery for quick replacement without removing the sight or losing zero. CNC-machined from aircraft-grade 7075-T6 aluminum, the Osight SE DPP delivers a durable, intuitive shooting experience in a compact, streamlined design.



FEATURES

- **Enclosed Emitter Optic:** With a fully enclosed system, Osight SE DPP offers unmatched protection against the elements, ensuring reliable performance in any environment.
- **Large Field of View:** Engineered with advanced anti-reflective lens coatings, this sight maximizes light transmission for unmatched clarity, allowing you to quickly lock onto targets with pinpoint precision. A 0.91" x 0.71" window delivers a greater sight picture, ensuring faster target acquisition and quicker follow-up shots.
- **Multi-Reticle System (2 MOA Dot & 32 MOA Circle):** Switch between dot-and-circle, 2 MOA dot-only, or 32 MOA circle-only reticles for any shooting scenario. Enjoy sharp clarity and strong contrast for precise, confident aiming.
- **DPP Footprint:** DPP footprint for broad compatibility, easy installation, and a secure, repeatable mount — no adapters or modifications needed.
- **Side-Loading CR1620 Battery:** Effortless battery replacement without removing the optic ensures hassle-free re-zeroing. A high-end CR1620 battery offers easy accessibility while maintaining steady performance.
- **Aspherical Lens:** The aspherical lens ensures zero distortion, parallax-free performance, and exceptional clarity for rapid, precise target acquisition.
- **Motion Activation Technology (MAT™):** The Osight SE DPP powers on at the slightest movement, and powers down after 3 minutes of inactivity to conserve battery.
- **Low Power Indication:** When battery voltage drops below 2.2V, the reticle will quickly triple-flash once per minute to recommend a battery replacement.
- **Sleek Battery Tray:** With a sleek and streamlined battery tray design, the Osight SE DPP stays comfortable to carry, quick to draw, and ideal for concealed use.
- **10 Brightness Settings:** 8 daylight and 2 night vision settings — compatible levels for versatility in any demands.
- **CNC-Machined Aircraft-Grade 7075-T6 Aluminum:** The optic is nearly indestructible with CNC-machined aircraft-grade 7075-T6 aluminum housing, ensuring durability and a professional edge over time.
- **Memory Function:** Once activated, the built-in memory function returns to the last selected brightness level, allowing users to focus on the target without distraction.

RUNTIME & BRIGHTNESS

Reticle	2 + 32 MOA	2 MOA Dot	32 MOA Circle
Mode 3			
	46,600 H	75,000 H	50,000 H

Settings	Night Vision	Day Light
Brightness	(Lowest) Level 1-2	Level 3-10 (Brightest)

SPECIFICATIONS


Optic	Osight SE DPP
Reticle Type	2 MOA Dot & 32 MOA Circle
Reticle Color	Red
Emitter	Enclosed
Light Wavelength	650 nm
Adjustment Per Click	1 MOA
W&E Travel Range	± 35 MOA
Battery Life	75,000 H (Mode 3 Dot-only)
Power Source	CR1620
Brightness Settings	8 DL & 2 NV
Window Size	0.91 × 0.71 in / 23 × 18 mm
Magnification	1×
Aspherical Lens	Yes
Parallax-Free	Yes
Unlimited Eye Relief	Yes
Motion Activation Technology (MAT™)	Yes
Memory Function	Yes
Multi-Coatings	Yes
Housing Material	CNC-Machined Aircraft-Grade 7075-T6 Aluminum
Waterproof Rating	IPX7
Dimensions	1.83 × 1.12 × 1.11 in / 46.4 × 28.5 × 28.2 mm
Weight	1.34 oz / 38 g

⚠ WARNING


- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours**.
- **KEEP** new and used batteries **OUT OF REACH** of **CHILDREN**.
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.



WATERPROOF IPX7



COMPLIANCE CAN ICES-003 (B) / NMB-003 (B)



WARRANTY



www.osight.com/lifetime-warranty

IN THE BOX

Optic (CR1620 battery included)	Screw Box
Adjustment Tool	Osight Sticker
READ ME Card	Cleaning Cloth
3 × M3*11.5 mm Screws	Safety Warnings
3 × M3*12.5 mm Screws	User Manual
3 × M4*10.5 mm Screws	
3 × M4*11.5 mm Screws	
3 × #6-32*0.472 in Screws	
3 × #6-40*0.413 in Screws	
3 × #6-40*0.488 in Screws	
2 × Spare Battery Compartment Screws	



Note: The Osight SE DPP MUST be mounted properly by applying non-permanent (medium/blue) threadlocker to the included screws. AND torque each screw to 15-17 in-lbs (suggested torque value in the READ ME card). If an adapter plate is required, please follow the manufacturer's installation instructions.



www.osight.com